

AHD5104

AHD DVR 4 Channel 5in1 1080N



- AHD DVR 4Channel Video BNC+ 4 Channel Audio RCA input
- 5 in 1; Supports AHD/TVI/CVI/CVBS/IP
- Video Output: 4*1080N, 4*720P, 4*960H
- Codec:H.264
- External Interface: 1 Ch VGA, 1Ch HDMI, 1 Ch RCA, 1*RS485, 2 USB ports 2.0, 1HDD SATA port (Max 8TB), RJ45 10M/100M
- supports web, CMS and mobile (iOS, Android) monitoring
- Support UTC, Control signal & video transmit through one single coaxial



| | |
|---------------------|--|
| System | |
| Main processor | Hi3520D V200 |
| Interface | |
| Operating interface | Support 16-bit true color graphical menu interface and mouse operation |
| Preview | 04-01-2018 |
| Codec | H.264 |
| Monitor quality | VGA?HDMI?HD |
| Preview ability | 4*1080N |
| Encode ability | 4*1080N |
| Decode ability | 1*1080N |
| Video | |
| Multi-mode input | Analog? 4*1080N? 4*720P?4*960, Hhybrid? 2*720P?analog?+2*720P?network?; network?8*1080P;12*960P; 8*720P;4*1080P;4*720P;1*1080P |
| Motion Detection | Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel) |
| Audio | |
| Audio compression | G.711A |
| Intercom | Support |
| Record & playback | |
| Record mode | manual>alarm>motion detection>timing |
| Local Playback | 4ch(analog input mode) |
| Search mode | Search by time, calendar, event, channel |
| Storage & backup | |



| | |
|---------------------------|---|
| Video storage | HDD, network |
| Backup mode | Network, USB hard disk, USB burner, SATA burner |
| External Interface | |
| Video input | 4ch BNC |
| Video output | 1ch VGA,1ch HDMI |
| Loop Vout | N/A |
| Audio input | 4ch RCA |
| Audio output | 1ch RCA |
| Alarm input | 0?Can be extended to 4ch? |
| Alarm output | 0?Can be extended to 1ch? |
| Network interface | RJ45 10M/100M |
| PTZ control | 1*RS485, Support kinds of PTZ protocols |
| USB | 2* USB 2.0 ports |
| HDD | 2*SATA ports (Max 8TB/per) |
| Wireless | 3G, WIFI (extend via USB) |
| General | |
| Power Supply | 12V/4A |
| Power consumption | <15W (without HDD) |
| Working environment | Temperature:0?—+55??Humidity:10%—90%?Atm:86kpa—106kpa |
| Dimension | 171mm*78mm |
| Weight | 135g |