

# AHD5108

## AHD DVR 8 Channel 5in1 1080N



- AHD DVR 8 Channle Video BNC+ 4 Channel Audio RCA input
- 5 in 1; Supports AHD/TVI/CVI/CVBS/IP
- Video Output: 8\*1080N; 4\*1080P
- Codec:H.264
- External Interface: 1 Ch VGA, 1Ch HDMI, 1 Ch RCA, 1\*RS485, 2 USB ports 2.0, 1HDD SATA port (Max 8TB), RJ45 10M/100M
- supports web, CMS and mobile (iOS, Android) monitoring
- Support UTC, Control signal & video transmit through one single coaxial



System	
Main processor	Hi3520D V300
Interface	
Operating interface	Support 16-bit true color graphical menu interface and mouse operation
Preview	04-01-2018
Codec	H.264
Monitor quality	VGA?HDMI?HD
Preview ability	8*1080N
Encode ability	8*1080N@12fps/4*1080P@15fps
Decode ability	8*1080N@12fps/4*1080P@15fps
Video	
Multi-mode input	analog? 8*1080N? 4*1080P, hybrid? 2*1080P?analog?+2*1080P?network?; 4*1080N?analog?+4*960P?network ), network?16*1080P; 9*1080P;16*960P; 4*5M
Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel)
Audio	
Audio compression	G.711A
Intercom	Support
Record & playback	
Record mode	manual>alarm>motion detection>timing
Local Playback	8ch(analog input mode)
Search mode	Search by time, calendar, event, channel

Storage & backup	
Video storage	HDD, network
Backup mode	Network, USB hard disk, USB burner, SATA burner
External Interface	
Video input	8ch BNC
Video output	1ch VGA,1ch HDMI
Loop Vout	N/A
Audio input	4?Can be extended to 8ch?RCA
Audio output	1ch RCA
Alarm input	0?Can be extended to 4ch?
Alarm output	0?Can be extended to 1ch?
Network interface	RJ45 10M/100M
PTZ control	1*RS485, Support kinds of PTZ protocols
USB	2* USB 2.0 ports
HDD	2*SATA ports (Max 8TB/per)
Wireless	3G, WIFI (extend via USB)
General	
Power Supply	12V/4A
Power consumption	<15W (without HDD)
Working environment	y
Dimension	200mm*78mm
Weight	196g