

# AC200

## Fail Safe Electric Bolt Lock



- Fail Safe Electric Bolt Lock
- Suitable for metal, glass or wooden door
- Low Temperature, safe & Durable
- Fail Safe: Locked when energized (NC)
- Low Power Consumption
- MOV Provides Reverse Current Protection
- Superior Strength Aluminum Alloy, Solid Stainless Steel Bolt
- Auto-relock if no Action within 5 sec
- Long Life with 500000 Operations
- The Photoelectricity Control Technology, prevent the machanical defect

Specification	
Fail Safe:	Lock When energized
Face place material:	High Aluminum, Carrulous Line Finished
Operating Humidity:	0~90%(non-condensing)
Operating temp:	-10~+25?(14-131F)
Induction Distance:	8mm
Surface Temp:	<20*c
Solenoid:	Continuous duty
Holding force:	1000kg
Current:	Start: 0.9A, Standby: 0.15A
Voltage:	DC12V
Lock pin:	16mmDIA, stainless steel out throw16mm
Magnet bracket:	90Lx24Wx3H(mm)
Blot out plate size:	210Lx42Wx0.8H(mm)
Face plate size:	200Lx34Wx3.4H(mm)
Lock body size:	157.5Lx31Wx40H(mm)
Weight:	0.7kg